Kraus & Naimer



Sample image

Datasheet

Article number: 70010788
Designation: KG20B.T206/40.KL11V
Description: Switch Global Disconnector

IEC 60947-3 EN 60947-3, VDE 0660 Teil 107

Rated insulation voltage Ui

Voltage (V)	AC / DC
690	50/60Hz

Rated uninterrupted current Iu/Ith

Current (A)	Ambient temperature (°C)	Peak temperature (°C)	additional requirements
25	50	55	Ambient temperature +50°C during 24 hours with peaks up to +55°C

Rated operational current Ie

Utilization category	Voltage (V)	Current (A)
AC-32A	20 - 400	20

Rated operational power

Utilization category	Voltage (V)	No. of phases	No. of poles	Power (kW)
AC-3	220 - 240	3	3	4
AC-3	380 - 440	3	3	5,50
AC-3	660 - 690	3	3	5,50
AC-23A	220 - 240	3	3	5,50
AC-23A	380 - 440	3	3	7,50
AC-23A	660 - 690	3	3	7,50

Max. Fuse rating IEC

Fuse characteristic	No. of Fuses	Current (A)
gG	1	35

UL60947-4-1 , UL508

Nominal Voltage

Voltage (V)	AC / DC
600	AC

Rated insulation voltage Ui

Voltage (V)	AC / DC
600	AC

Rated thermal current

Current (A)	Ambient temperature (°C)	Additional Text
25	0 - 40	--

Horsepower rating

Across-the-Line Motor Starting	Voltage (V)	No. of phases	No. of poles	Power (HP)	Ambient temperature [°C]
DOL	110 - 120	1	2	1	40
DOL	220 - 240	1	2	3	40
DOL	277 - 277	1	2	3	40
DOL	415 - 415	1	2	5	40
DOL	440 - 480	1	2	5	40
DOL	550 - 600	1	2	5	40
DOL	110 - 120	3	3	2	40
DOL	200 - 240	3	3	7,50	40
DOL	415 - 415	3	3	10	40
DOL	440 - 480	3	3	15	40
DOL	550 - 600	3	3	20	40

Pilot duty rating code

Duty Code
A600

SCCR / Max. fuse rating

Conditions of acceptability

This device is suitable for use on circuits capable of delivering not more than 10kA rms symmetrical amperes, 600V ac max. when protected by Type RK1 fuses.
Suitable for use on a circuit capable of delivering not more than 65000 rms symmetrical amperes at 600V max., when protected by 40A Class J fuses.

Temp. rating of wire

Temperature rating (°C)	Current (A)	Text
60 - 75	--	--

General Use

AC / DC	Voltage (V)	Current (A)	No. of phases	No. of poles	No. of contacts in series
AC	277	25	1	1	1
AC	600	25	1	2	1
AC	600	25	3	3	1

General Information

Text

- The operating handle and position indicating means to be used with these manual motor controllers should be provided from the manufacturer, or the operating handle and position indicating means to be used should have been previously evaluated in combination with the manual motor controllers.

Kraus & Naimer

General Information

Text

- When intended for use as a motor disconnector the device shall be provided with a method of being locked in the OFF-position.

CSA

Nominal Voltage

Voltage (V)	*AC / DC*
600	AC

Rated insulation voltage Ui

Voltage (V)	*AC / DC*
600	AC

Rated thermal current

Current (A)	*Ambient temperature (°C)*	*Additional Text*
25	0 - 40	--

Horsepower rating

Across-the-Line Motor Starting	*Voltage (V)*	*No. of phases*	*No. of poles*	*Power (HP)*	*Ambient temperature [°C]*
DOL	110 - 120	1	2	1	40
DOL	220 - 240	1	2	3	40
DOL	277 - 277	1	2	3	40
DOL	415 - 415	1	2	5	40
DOL	440 - 480	1	2	5	40
DOL	550 - 600	1	2	5	40
DOL	110 - 120	3	3	2	40
DOL	220 - 240	3	3	7,50	40
DOL	415 - 415	3	3	10	40
DOL	440 - 480	3	3	15	40
DOL	550 - 600	3	3	20	40

Pilot duty rating code

Duty Code
A600

Temp. rating of wire

Temperature rating (°C)	*Current (A)*	*Text*
75	--	--

General Use

AC / DC	*Voltage (V)*	*Current (A)*	*No. of phases*	*No. of poles*	*No. of contacts in series*
AC	277	25	1	1	1
AC	600	25	1	2	1
AC	600	25	3	3	1


GENERAL TECHNICAL INFORMATION

Size of conductor

composition of conductor	*Min. / Max. value*	*No. of conductor per terminal*	*Cross section (mm²) or (AWG/kcmil)*	*Material of the wire*
Flexible wire	Max.	1	AWG 10	Copper
Flexible wire	Max.	1	4mm²	Copper
Single-core or stranded wire	Max.	1	6mm²	Copper
Single-core or stranded wire	Max.	1	AWG 10	Copper
Flexible wire with sleeve	Max.	1	4mm²	Copper

Stripping length

Length (mm)	--



Recommended screw driver

Type of screw driver	*Value*
Cross Screwdriver	PH2
Slot screwdriver according to DIN 5264	0,8x4

Tightening torque of screws

tightening torque (Nm)	*tightening torque (lb-in)*
1,25	11

Approbations

Specification	*Marking*
CE marking	
UK Directives	
UL 60947-4-1; CSA C22.2 No. 60947-4-1	
CSA C.22.2 No.14	
GB/T14048.3	

General Information


Text

- Use solo alambres de cobre con o sin alambres individuales chapados en estaño/plata. No se permite el estañado posterior de los extremos del conductor.
- EMC Note: This device is suitable for use in environment A and B.
- Terminals with factory fitted jumper links are tightened during production for loss prevention. When opening the terminal clamps, make sure that no factory fitted links get lost and that all wire connections are properly seated.

General Information	
Text	
- After wiring, ALL terminal screws must be tightened to the specified torque values.	
- La clase de protección del tipo de montaje seleccionado puede variar si se utilizan extras opcionales.	
- Do not lubricate or treat contacts.	
- Switches may only be mounted, connected and set into operation by qualified persons according to the accepted rules of technology.	
Waste Electrical & Electronic Equipment (WEEE)	
Picture name	*Description*
	Do not throw in the trash as care must be taken to ensure environmentally sound disposal and recycling. Please either use an environmentally friendly waste disposal company; return to the supplier for disposal; or return direct to the manufacturer, Kraus & Naimer. You can find local Kraus & Naimer offices at www.krausnaimer.com
Proposition 65	
Picture name	*Description*
	WARNING: This product can expose you to chemicals including nickel and lead, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Classification Contact: Rigid contact bridge
Classification Contact Mat: Silver
Classification Terminal: Screw terminal

Mounting-KL11V




IP - Code front side		IP66, IP67, IP69k
Stages		6,00 - 6,00
A	⊢	190,00 mm
B	⊢	100,00 mm
C	⊢	178,00 mm
D2	⌀	4,00 x M25
D3	⌀	5,60 mm
D6	⌀	2,00 x M25
H	⊢	93,00 mm

Kraus & Naimer

Wiring diagram

KG20B.T306.KL11V



Kraus & Naimer


Switch program

KG20B.T306.KL11V

Kraus & Naimer

KG20B	T306	Page 1 of 1

Face Plate




		1L1	1L2	1L3	2L1	2L2	2L3		
		1	3	5	7	9	11	13	15
Switching Angle 90		2	4	6	8	10	12	14	16
Total switching Angle 90		1T1	1T2	1T3	2T1	2T2	2T3		
0	270								
1	0	■	■	■	■	■	■		
	90								
	180								

Version: 117

Kraus & Naimer

Face plate

S1.F656/E10.V9



Kraus & Naimer

HANDLES

Designation: S1B.G842
Handle colour: "2" red

GENERAL TECHNICAL INFORMATION	
Recommended screw driver	
Type of screw driver	*Value*
Cross Screwdriver	PH1
Slot screwdriver according to DIN 5264	0,8x5,5

Kraus & Naimer

AUXILIARY CONTACTS

(cam operated) for switch type KG20 - KG100C

Designation: K0.M510A/4CA-B
Number of contacts: "4" 2 auxiliary contacts (for dual drive)
Operation of contacts: "C" 1 auxiliary contact closed in pos. 1 and 1 auxiliary contact closed in pos. 0 (NO/NC)
Type of version: "A" 1. auxiliary contact module
Type of mounting: "-B" for type of mounting VE, VE2, silver contacts

IEC 60947-3 EN 60947-3, VDE 0660 Teil 107

Nominal Voltage

Voltage (V)	*AC / DC*
440	AC

Rated uninterrupted current Iu/Ith

Current (A)	*Ambient temperature (°C)*	*Peak temperature (°C)*	*additional requirements*
10	55	60	Ambient temperature +55°C during 24 hours with peaks up to +60°C

Rated operational current Ie

Utilization category	*Voltage (V)*	*Current (A)*
AC-15	110 - 240	2,50
AC-15	380 - 440	1,50
AC-21A	440	10

UL60947-4-1 , UL508

Rated thermal current

Current (A)	*Ambient temperature (°C)*	*Additional Text*
10	0 - 40	--

GENERAL TECHNICAL INFORMATION

Size of conductor

composition of conductor	*Min. / Max. value*	*No. of conductor per terminal*	*Cross section (mm²) or (AWG/kcmil)*	*Material of the wire*
Solid wire	Min.	1	0.5mm²	Copper
Solid wire	Min.	2	0.5mm²	Copper
Flexible wire	Min.	1	0.75mm²	Copper
Flexible wire	Min.	2	0.75mm²	Copper
Flexible wire	Max.	2	AWG 16	Copper
Flexible wire	Max.	2	1.5mm²	Copper
Single-core or stranded wire	Max.	2	AWG 14	Copper
Single-core or stranded wire	Max.	2	1.5mm²	Copper
Flexible wire with ferrule according to DIN 46228	Min.	1	0.5mm²	Copper
Flexible wire with ferrule according to DIN 46228	Max.	2	1mm²	Copper
Flexible wire with ferrule according to DIN 46228	Min.	2	0.5mm²	Copper

Stripping length

Length (mm)	--



Recommended screw driver

Type of screw driver	*Value*
Cross Screwdriver	PH1
Slot screwdriver according to DIN 5264	0,6x3,5

Tightening torque of screws

tightening torque (Nm)	*tightening torque (lb-in)*
0,40	3,50

Conditions during transport and storing


Minimum temperature (°C)	*Maximum temperature (°C)*	*additional requirements*
-40	85	In case of temperatures below -5°C no shock load permissible

General Information

Text

- Use solo alambres de cobre con o sin alambres individuales chapados en estaño/plata. No se permite el estañado posterior de los extremos del conductor.
- Terminals with factory fitted jumper links are tightened during production for loss prevention. When opening the terminal clamps, make sure that no factory fitted links get lost and that all wire connections are properly seated.
- After wiring, ALL terminal screws must be tightened to the specified torque values.
- Do not lubricate or treat contacts.
- Switches may only be mounted, connected and set into operation by qualified persons according to the accepted rules of technology.

Classification Terminal: Screw terminal



A	=	42,00 mm	M	=	9,00 mm	